



TOYOラブレックスカップリング				軸径		ボス 外径 Dn	全幅 L	フランジ (mm)					許容 回転数 rpm	許容 トルク N-m	重量 W (kg)
サイズ 番号	在庫	ゴム タイヤ	在庫	最小 d	最大 d			長さ H	外径 Df	間隙					
								Z1	Z2	Z3					
RF-60	◎	RF-60T	◎	8	12	20	32	10.3	44	11	5	25	4,000	9.8	0.28
RF-100	◎	RF-100T	◎	10	22	38	66	26	80	14	10	40	4,000	29	1.21
RF-135	◎	RF-135T	◎	16	30	48	90	35	108	20	14	53	4,000	78	2.87
RF-180	◎	RF-180T	◎	23	35	64	120	46	144	28	20	70	3,000	147	6.38
RF-210	◎	RF-210T	◎	28	50	78	143	54	168	35	27	83	3,000	294	9.40
RF-265	◎	RF-265T	◎	33	60	95	178	67	210	44	32	105	2,000	736	19.0
RF-310	◎	RF-310T	◎	36	70	112	208	75	248	58	36	121	2,000	1,230	31.0
RF-400		RF-400T	◎	40	85	145	270	100	320	70	44	153	1,600	2,700	70.0
RF-450		RF-450T	◎	55	100	165	300	110	360	80	50	171	1,250	4,900	101
RF-550		RF-550T	◎	90	130	200	365	130	440	105	53	196	1,000	9,810	170
RF-700		RF-700T		100	160	255	460	165	560	130	70	256	800	19,600	358